


Welding Neck flange Type 11
EN1092-1 P245GH,P250GH
Ex.DIN 2631 - 2635

Nom. Dia. DN	d1	D	d3	s	b	r	k	h	holes	d2	d4	theor.weight kg/pc
PN 40												
15	21,3	95	32	2	16	4	65	38	4	14	45	0,75
20	26,9	105	40	2,3	18	4	75	40	4	14	58	1,06
25	33,7	115	46	2,6	18	4	85	40	4	14	68	1,29
32	42,4	140	56	2,6	18	6	100	42	4	18	78	1,88
40	48,3	150	64	2,6	18	6	110	45	4	18	88	2,33
50	60,3	165	75	2,9	20	6	125	48	4	18	102	2,82
65	76,1	185	90	2,9	22	6	145	52	8	18	122	3,74
80	88,9	200	105	3,2	24	8	160	58	8	18	138	4,75
100	114,3	235	134	3,6	24	8	190	65	8	22	162	6,52
125	139,7	270	162	4-6,3mm	26	8	220	68	8	26	188	9,07
150	168,3	300	192	4,5-7,1mm	28	10	250	75	8	26	218	11,80
200	219,1	375	244	6,3-8,8mm	34	10	320	88	12	30	285	21,50
250	273	450	306	7,1-10mm	38	12	385	105	12	33	345	34,90
300	323,9	515	362	8-10mm	42	12	450	115	16	33	410	49,70
350	355,6	580	510	8-10mm	46	12	510	125	16	36	465	69,30
400	406,4	660	585	10-12,5mm	50	12	585	135	16	39	535	98,00
450	457	685	610	10-12,5mm	57	12	610	135	20	39	560	105,00
500	508	755	670	10-12,5mm	57	12	670	145	20	42	615	130,00