



EN 10253-2 Short Radius - seamless
 EN1025 -2, P235GH, P265GH, P355NL, P355QH

Nom. Dia. DN	Std. XS XXS	D		S		r		theor. weight kg/pc	30° or 45°	90°	60° or 180°
		mm	inch	mm	inch	mm	inch				
50		60,3		2,90		51		0,3		✓	
		60,3		4,00		51		0,45		✓	
		60,3		5,60		51		0,60		✓	
		60,3		7,10		51		0,85		✓	
65		76,1		2,90		63		0,70		✓	
		76,1		4,00		63		0,80		✓	
		76,1		5,60		63		1,00		✓	
		76,1		7,10		63		1,44		✓	
80		88,9		4,00		76		1,30		✓	
		88,9		5,60		76		1,28		✓	
		88,9		8,00		76		1,83		✓	
100		114,3		3,60		102		1,20		✓	
		114,3		4,50		102		2,00		✓	
		114,3		6,30		102		2,76		✓	
		114,3		8,80		102		3,70		✓	
		114,3		11,00		102		7,05		✓	
125		139,7		4,50		127		2,80		✓	
		139,7		6,30		127		3,10		✓	
		139,7		10,00		127		6,40		✓	
150		168,3		4,50		152		4,70		✓	
		168,3		7,10		152		6,80		✓	
		168,3		11,00		152		10,20		✓	
		168,3		12,50		152		11,70		✓	
200		219,1		6,30		203		11,00		✓	
		219,1		8,00		203		15,00		✓	
		219,1		12,50		203		21,00		✓	
250		274		7,10		254		20,00		✓	
		273		10,00		254		26,00		✓	
		273		12,50		254		32,50		✓	
		273		16,00		254		39,00		✓	
300		323,9		7,10		305		29,00		✓	
		323,9		10,00		305		33,00		✓	
		323,9		12,50		305		47,00		✓	
		323,9		17,50		305		60,00		✓	
350		355,6		10,00		356		47,50		✓	
		355,6		12,50		356		60,00		✓	
		355,6		19,00		356		80,00		✓	

400		406,4	10,00	406	63,00	√
		406,4	12,50	406	79,00	√
		406,4	21,50	406	125,00	√
450		457	10,00	406	81,00	√
		457	12,50	406	100,00	√
500		508	10,00	508	98,00	√
		508	12,50	508	124,00	√
600		610	10,00	610	158,00	√
		610	12,50	610	176,00	√