


Blind flange Type 05 , Facing type B1 (Raised Face) EN 1092-1

S235JR, P245GH, 304(L), 316(L)

Ex.DIN 2573 - 2576

Nom. Dia. DN	D	G	K	B	holes	L	Teor.weight pc/kg
PN 6 - and PN2,5 differ from DN1200incl. upwards							
450	595	520	550	24	16	22	51,2
500	654	570	600	24	20	22	60
600	755	670	705	30	20	26	103
700	860	775	810	40	24	26	178
800	975	880	920	44	24	30	252
900	1075	980	1020	48	24	30	336
1000	1175	1080	1120	52	28	30	435
PN10							
450	615	532	565	28	20	26	63
500	670	585	620	28	20	26	75
600	780	685	725	34	20	30	124
700	895	800	840	38	24	30	183
800	1015	905	950	48	24	33	297
900	1115	1005	1050	50	28	33	374
1000	1230	1110	1160	54	28	36	492
PN16							
450	640	550	585	40	20	30	96,6
500	715	610	650	44	20	33	133
600	840	725	770	54	20	33	226
700	910	795	840	58	24	36	285
800	1025	900	950	62	24	39	388
900	1125	1000	1050	64	28	39	483
1000	1255	1115	1170	68	28	42	640

* - internal diameter of the flanges must be agreed prior order.