



## Welding Neck flange Type 11

EN1092-1 P245GH,P250GH

Ex.DIN 2631 - 2635

Nom. Dia. DN	d1	D	d3	s	b	r	k	h	holes	d2	d4	theor.weight kg/pc
<b>PN 10</b>												
15	21,3	95	32	2	16	4	65	38	4	14	45	0,770
20	26,9	105	40	2,3	18	4	75	40	4	14	58	1,090
25	33,7	115	46	2,6	18	4	85	40	4	14	68	1,300
32	42,4	140	56	2,6	18	6	100	42	4	18	78	1,910
40	48,3	150	64	2,6	18	6	110	45	4	18	88	2,150
50	60,3	165	74	2,9-7mm	18	6	125	45	8	18	102	2,53
65	76,1	185	92	2,9-8mm	18	6	145	45	8	18	122	3
80	88,9	200	105	3,2-8,8mm	20	6	160	50	8	18	138	3,92
100	114,3	220	131	3,6-10mm	20	8	180	52	8	18	158	4,62
125	139,7	250	156	4-10mm	22	8	210	55	8	18	188	6,30
150	168,3	285	184	4,5-12,5mm	22	10	240	55	8	22	212	7,8
200	219,1	340	234	5,9-12,5mm	24	10	295	62	8	22	268	11,60
250	273	395	292	6,3-12,5mm	26	12	350	68	12	22	320	15,80
300	323,9	445	342	7,1-12,5mm	26	12	400	68	12	22	370	18,30
350	355,6	505	385	10-12,5mm	26	12	460	68	16	22	430	25,3
400	406,4	565	440	10-12,5mm	26	12	515	72	16	26	482	30,6
450	457	615	488	10-12,5mm	28	12	565	72	20	26	532	35,1
500	508	670	542	10-12,5mm	28	12	620	75	20	26	585	40,5
600	610	780	642	10-12,5mm	30	12	725	82	20	30	685	53