



## Welding Neck flange Type 11

EN1092-1 P245GH,P250GH

Ex.DIN 2631 - 2635

Nom. Dia. DN	d1	D	d3	s	b	r	k	h	holes	d2	d4	theor.weight kg/pc
<b>PN 6</b>												
15	21,3	80	30	2	12	4	55	30	4	11	40	0,410
20	26,9	90	38	2,3	14	4	65	32	4	11	50	0,620
25	33,7	100	42	2,6	14	4	75	35	4	11	60	0,730
32	42,4	120	55	2,6	14	6	90	35	4	14	70	1,110
40	48,3	130	62	2,6	14	6	100	38	4	14	80	1,260
50	60,3	140	74	2,9-7mm	14	6	110	38	4	14	90	1,43
65	76,1	160	88	2,9-8mm	14	6	130	38	4	14	110	1,77
80	88,9	190	102	3,2-8,8mm	16	8	150	42	4	18	128	2,88
100	114,3	210	130	3,6-10mm	16	8	170	45	4	18	148	3,41
125	139,7	240	155	4-10mm	18	8	200	48	8	18	178	4,65
150	168,3	265	184	4,5-12,5mm	18	10	225	48	8	18	202	5,5
200	219,1	320	236	5,9-12,5mm	20	10	280	55	8	18	258	8,60
250	273	375	290	6,3-12,5mm	22	12	335	60	12	18	312	11,70
300	323,9	440	342	7,1-12,5mm	22	12	395	62	12	22	365	15,30
350	355,6	490	385	10-12,5mm	22	12	445	62	12	22	415	20,3
400	406,4	540	438	10-12,5mm	22	12	495	65	16	22	465	23,1
450	457	595	492	10-12,5mm	22	12	550	65	16	22	520	27
500	508	645	538	10-12,5mm	24	12	600	68	20	22	570	30,8
600	610	755	640	10-12,5mm	30	12	705	70	20	26	670	44