



Slip on plate flanges as per JIS2220 10K SS400, S235JR,  
304L,316L

Nom. Dia. DN	d1	D	b5	k	b	holes	d2	Teor.weight pc/kg
<b>10K</b>								
10	17,3	90	17,8	65	12	4	15	0,5
15	21,3	95	22,2	70	12	4	15	0,56
20	26,9	100	27,7	75	14	4	15	0,72
25	33,7	125	34,5	90	14	4	19	1,12
32	42,4	135	43,5	100	16	4	19	1,47
40	48,3	140	49,5	105	16	4	19	1,55
50	60,3	155	61,5	120	16	4	19	1,86
65	76,1	175	77,5	140	18	4	19	2,58
80	88,9	185	90,5	150	18	8	19	2,6
100	114,3	210	115,5	175	18	8	19	3,1
125	139,7	250	141,5	210	20	8	23	4,73
150	168,3	280	170,5	240	22	8	23	6,3
200	219,1	330	221,5	290	22	12	23	7,46
250	273,0	400	276,5	355	24	12	25	11,8
300	323,9	445	327,5	400	24	16	25	27,8
350	355,6	490	359	445	26	16	25	16,3
400	406,4	560	411,0	510	28	16	27	23,3
450	457,0	620	461	565	30	20	27	29,3
500	508	675	511	620	30	20	27	33,3
550	558	745	562,0	680	32	20	33	43
600	610	795	615,0	730	32	24	33	45,4