



Slip on plate flanges as per JIS2220 5K SS400, S235JR,
304L,316L

Nom. Dia. DN	d1	D	b5	K	b	holes	d2	Teor.weight pc/kg
5K								
10	17,3	75	17,8	55	9	4	12	0,26
15	21,3	80	22,2	60	9	4	12	0,3
20	26,9	85	27,7	65	10	4	12	0,36
25	33,7	95	34,5	75	10	4	12	0,45
32	42,4	115	43,5	90	12	4	15	0,77
40	48,3	120	49,5	95	12	4	15	0,82
50	60,3	130	61,5	105	14	4	15	1,06
65	76,1	155	77,5	130	14	4	15	1,48
80	88,9	180	90,5	145	14	4	19	1,97
100	114,3	200	115,5	165	16	8	19	2,35
125	139,7	235	141,5	200	16	8	19	3,2
150	168,3	265	170,5	230	18	8	19	4,4
200	219,1	320	221,5	280	20	8	23	6,24
250	273,0	385	276,5	345	22	12	23	9,4
300	323,9	430	327,5	390	22	12	23	10,2
350	355,6	480	359	435	24	12	25	14
400	406,4	540	411,0	495	24	16	25	16,9
450	457,0	605	461	555	24	16	25	21,4
500	508	655	511	605	24	20	25	23
550	558	720	562,0	665	26	20	27	30,1
600	610	770	615,0	715	26	20	27	32,5