



Blind flange Type 05 , Facing type B1 (Raised Face) EN 1092-1
 PN16/10 S235JR, P245GH, 304(L), 316(L)

Nom. Dia. DN	D	G	k	B	holes	L	Teor.weight pc/kg
PN 10							
DN 15 - DN40 dimensions identical with PN40 , DN50 - DN150 dimensions identical with PN16							
200	340	268	295	24	8	22	16,5
250	395	320	350	26	12	22	24,1
300	445	370	400	26	12	22	30,8
350	505	430	460	26	16	22	39,6
400	565	482,0	515	26	16	26	49,4
PN16							
DN15 - DN40 dimensions identical with PN40							
50	165	102	125	18	4	18	2,88
65	185	122	145	18	8	18	3,5
80	200	138	160	20	8	18	4,61
100	220	158	180	20	8	18	5,65
125	250	188	210	22	8	18	8,13
150	285	212	240	22	8	22	10,5
200	340	268	295	24	12	22	16,2
250	405	320	355	26	12	26	25
300	460	378	410	28	12	26	35
350	520	438	470	30	16	26	48
400	580	490	525	32	16	30	63,5
PN40							
	D	G	k	B	holes	L	
15	95	45	65	16	4	14	0,813
20	105	58	75	18	4	14	1,14
25	115	68	85	18	4	14	1,38
32	140	78	100	18	4	18	2,03
40	150	88	110	18	4	18	2,35
50	165	102	125	20	4	18	3,2
65	185	122	145	22	8	18	4,3
80	200	138	160	24	8	18	5,54
100	235	162	190	24	8	22	7,6
125	270	188	220	26	8	26	10,8
150	300	218	250	28	8	26	14,6
200	375	285	320	36	12	30	28,8
250	450	345	385	38	12	33	44,4
300	515	410	450	42	16	33	64,2
350	580	465	510	46	16	36	89,5
400	660	535	585	50	16	39	127