



Welding Neck flange Type 11

EN1092-1 P245GH,P250GH

Ex.DIN 2631 - 2635

Nom. Dia. DN	d1	D	d3	s	b	r	k	h	holes	d2	d4	theor.weight kg/pc
PN 25												
15	21,3	95	32	2	16	4	65	38	4	14	45	0,75
20	26,9	105	40	2,3	18	4	75	40	4	14	58	1,06
25	33,7	115	46	2,6	18	4	85	40	4	14	68	1,29
32	42,4	140	56	2,6	18	6	100	42	4	18	78	1,88
40	48,3	150	64	2,6	18	6	110	45	4	18	88	2,33
50	60,3	165	75	2,9	20	6	125	48	4	18	102	2,82
65	76,1	185	90	2,9	22	6	145	52	8	18	122	3,74
80	88,9	200	105	3,2	24	8	160	58	8	18	138	4,75
100	114,3	235	134	3,6	24	8	190	65	8	22	162	6,52
125	139,7	270	162	4-6,3mm	26	8	220	68	8	26	188	9,07
150	168,3	300	192	4,5-7,1mm	28	10	250	75	8	26	218	11,80
200	219,1	360	244	6,3-8,8mm	30	10	310	80	12	26	278	21,50
250	273	425	298	7,1-10mm	32	12	370	88	12	30	335	34,90
300	323,9	485	352	8-10mm	34	12	430	92	16	30	395	49,70
350	355,6	555	398	8-10mm	38	12	490	100	16	33	450	69,30
400	406,4	620	452	10-12,5mm	40	12	550	110	16	36	505	98,00
450	457	670	500	10-12,5mm	46	12	600	110	20	36	555	105,00
500	508	730	558	10-12,5mm	48	12	660	125	20	36	615	130,00