



**Welding Neck flange Type 11**

**EN1092-1 P245GH,P250GH**

**Ex.DIN 2631 - 2635**

Nom. Dia. DN	d1	D	d3	s	b	r	k	h	holes	d2	d4	theor.weight kg/pc
<b>PN 16</b>												
15	21,3	95	32	2	16	4	65	38	4	14	45	0,746
20	26,9	105	40	2,3	18	4	75	40	4	14	58	1,060
25	33,7	115	46	2,6	18	4	85	40	4	14	68	1,290
32	42,4	140	56	2,6	18	6	100	42	4	18	78	1,880
40	48,3	150	64	2,6	18	6	110	45	4	18	88	2,330
50	60,3	165	75	2,9-7mm	18	6	125	45	4	18	102	2,53
65	76,1	185	90	2,9-8mm	18	6	145	45	4	18	122	3,06
80	88,9	200	105	3,2-8,8mm	20	8	160	50	8*	18	138	3,70
100	114,3	220	131	3,6-10mm	20	8	180	52	8	18	158	4,62
125	139,7	250	156	4-10mm	22	8	210	55	8	18	188	6,30
150	168,3	285	184	4,5-12,5mm	22	10	240	55	8	22	212	7,75
200	219,1	340	235	5,9-12,5mm	24	10	295	62	12	22	268	11,00
250	273	405	292	6,3-12,5mm	26	12	355	70	12	26	320	15,60
300	323,9	460	344	7,1-12,5mm	28	12	410	78	12	26	378	22,00
350	355,6	520	390	10-12,5mm	30	12	470	82	16	26	438	32,8
400	406,4	580	445	10-12,5mm	32	12	525	82	16	30	490	41,1
450	457	640	490	10-12,5mm	34	12	585	83	20	30	550	50,6
500	508	715	548	10-12,5mm	36	12	650	84	20	33	610	66,2
600	610	840	670	10-12,5mm	40	12	770	88	20	36	720	104