



**Welding Neck flange Type 11**  
**EN1092-1 P245GH,P250GH**  
**Ex.DIN 2631 - 2635**

Nom. Dia. DN	d1	D	d3	s	b	r	k	h	holes	d2	d4	theor.weight kg/pc
<b>PN 63</b>												
15	21,3	105	34	2-5mm	20	4	75	45	4	14	45	1,20
20	26,9	130	42	2,3-6mm	22	4	90	48	4	18	58	2,02
25	33,7	140	52	2,6-6,3mm	24	4	100	58	4	18	68	2,63
32	42,4	155	62	2,6-6,3mm	24	6	110	60	4	22	78	3,20
40	48,3	170	70	2,6-6,3mm	26	6	125	62	4	22	88	4,07
50	60,3	180	82	2,9-7,1mm	26	6	135	62	4	22	102	4,51
65	76,1	205	98	2,9-8mm	26	6	160	68	8	22	122	5,58
80	88,9	215	112	3,2-8,8mm	28	8	170	72	8	22	138	6,68
100	114,3	250	138	3,6-11mm	30	8	200	78	8	26	162	9,27
125	139,7	295	168	6,3-12,5mm	34	8	240	88	8	30	188	14,50
150	168,3	345	202	6,3-12,5mm	36	10	280	95	8	33	218	21,40
200	219,1	415	256	6,3-12,5mm	42	10	345	110	12	36	285	34,10
250	273	470	316	7,1-15mm	46	12	400	125	12	36	345	48,30
300	323,9	530	372	8-17,5mm	52	12	460	140	16	36	410	67,50
<b>PN 100</b>												
<b>DN15 - DN40 same as PN63</b>												
50	60,3	195	90	2,9-7,1mm	28	6	145	68	4	26	102	5,82
65	76,1	220	108	2,9-8mm	30	6	170	76	8	26	122	7,57
80	88,9	230	120	3,2-8,8mm	32	8	180	78	8	26	138	8,82
100	114,3	265	150	3,6-11mm	36	8	210	90	8	30	162	13,10
125	139,7	315	180	6,3-12,5mm	40	8	250	105	8	33	188	21,00
150	168,3	355	210	6,3-12,5mm	44	10	290	115	12	33	218	28,30
200	219,1	430	278	6,3-12,5mm	52	10	360	130	12	36	285	50,20
250	273	505	340	7,1-15mm	60	12	430	157	12	39	345	81,40
300	323,9	585	400	8-17,5mm	68	12	500	170	16	42	410	118,00